





Single Circuit Tray | Thickness: 4mm 6 Splices Capacity

## 144F Fiber Optic Splice Closures

Single Circuit Max: 24 Trays, 24x6 Fibers



## **Features**

- Modular capacity up to 144 fibers
- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.

Sheath retention & central strength member fasten system

- included.
  - Closure construction and lightweight plastic provides
- strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware is included
- Protection class: IP68
- RoHS compliance



## **Application**

Underground, Aerial, Vault, Pole Mounting and Wall Mountable













## **Specifications**

Model No.

Model No.

Spliced Fiber Storage Capacity Size | Height x Width x Depth

Cable Ports

YT01059 | SSC-420180-2P-144-24T/24T-T6SC

420x180m, 144 Fibers Capacity, 24 Trays, 2 Port, Enclosure , w/o Mounting Kits

YT01060 | SSC-420180-2P-96-16T/24T-T6SC

420x180m, 96 Fibers Capacity, 16 Trays, 2 Port, Enclosure, w/o Mounting Kits

144 splices (24x6)

420mm x 180mm x 150mm

1 oval port (20mm), 2 round ports (30mm)

**Mounting Kits** 

See Other Document

Wall Mounting Kit - 1

Pole Mounting Kit - 1