


LC Duplex Polarity Reversible Uniboot Patch Cord | Single Mode

UNI20 Series with Push-Pull Boot Mechanism


The LC uniboot fiber patch cable have a duplex UNI20 series single-mode LC connector on each side. The patch cord utilises a special round duplex cable that allows duplex transmission within a single 1.2mm/2.5mm cable.

This uniboot LC duplex patch cord has easy Push-Pull connectors for quicker patching, and the polarity of its connectors can be switched by simply opening the connector's housing.




Connector Features

- Effortless release, using the push-pull boot mechanism
- Reduced cable tangling due to undivided duplex cords
- Detachable casing makes polarity reversal rather simple
- Compatible with cable diameters from 1.2 mm to 2.5 mm
- IEC61754-20 and GR-326-Core compliant
- RoHS/REACH&UL94-V0 inflammability compliant




Polarity Reversal

- Release the locking clamp
- Hold the connectors and pull back outer housing
- Remove the connectors from their slots gently, to avoid any damage and reverse the connectors' positions and reinstall them
- Return the housing back until it snaps



Dimensions



Unit of measurement: mm

Connector Specifications

LC Connector Compliance	IEC 61754-20 GR-326-Core RoHS
Alignment Technology	Full ceramic ferrule (Zirconia ZrO ₂)
Operating Temperature	-40°C to +85°C
Flammability	UL94 V-0
Durability	< 0.2 dB typical change for > 500 matings

Cable Specifications

- 2 cores round duplex fiber optic cable
- 2.0mm diameter
- Max. Tensile Strength is 300 N
- Min. Bending Radius is 15 mm
- Cable Color: Yellow

Optical Performance

Insertion Loss IEC 61300-3-4 Method B	Single Mode:	≤ 0.30dB Max. 0.15dB Typ.
	Return Loss IEC61300-3-6 Method B	Single Mode UPC: ≥ 50dB Single Mode APC: ≥ 60dB

Color Coding



LC-UPC A2 Blue



LC-APC A2 Green

End-face Control Parameters

Geometry Inspection	UPC : IEC 61755-3-1 APC : IEC 61755-3-2
Visual Inspection	IEC 61300-3-35

Order Coding

I - PC - 02 - RND - 020 - A2 - LC(UNI20) - LC(UNI20) - 005M

Type	Type	Fiber Count	Cable Type	Diameter	Fiber Type	1. Connector	2. Connector	Length
Indoor: I	Patch Cord: PC	2 Fibers: 02	Round: RND	2.0 mm: 020	SM G.657 A2: A2	LC-UPC: LC(UNI20) LC-APC: LA(UNI20)	LC-UPC: LC(UNI20) LC-APC: LA(UNI20)	___ M