

Fiber Optic Closures

36F Fiber Optic Outdoor Termination Box

3 Trays, 3x12 Fibers

Features

- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.
- Sheath retention & central strength member fasten system e. included.
- Ribbed closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- Re-enterable and reusable
- All hardware is included
- Protection class: IP65
- RoHS compliance

Components

- Cover
- Seal gasket
- Splice Tray
- Cable fixing device
- Nylon tie
- Buffer Tube

Optional Accessories

- Duct mounting kits
- Pole mounting kits

Bottom

Clamp

- Pressure valve
- Grounding device

Heat shrink sleeves

Grounding wire

Labeling paper

Installation tape



Specifications

Drop

Ports

Main

Port

Model No.	YT00979 OTB-362217-16P-36-3T-16
Size (L x W x H)	362mm x 217mm x 107mm
Spliced Fiber Capacity	36 splices (3 trays x12)
Adapter	16 SC SX/ LC DX adapters / 1x4, 1x8, 1x16 PLC splitter
Cable Ports (Cable Diameter)	Main ports 4 x 12mm
	Drop cables 16 x 5mm