


Components

- Cover
- Bottom
- Seal gasket
- Clamp
- Splice Tray (with heat shrink sleeves)
- Cable fixing device
- Grounding wire
- Nylon tie
- Labeling paper
- Buffer Tube
- Installation tape



144F Fiber Optic Outdoor Termination Box

6 Trays, 6x24 Fibers

Features

- Installation and reentry with a minimum of tools
- Easy to be opened or closed
- Re-enterable and reusable
- All hardware are captived
- Capable for loading 1:4, 1:8, 1:16 PLC splitter
- Capable for max. 16pcs SC or 32pcs LCadapters

Optional Accessories

- Duct mounting kits
- Pole mounting kits
- Pressure valve
- Grounding device



1 Tray - 16 SC adapters

4 Trays - No adapter

Main Port Drop Ports Main Port

Specifications

Model No.	OTB-305216-16P-144-6T-NA	OTB-305216-16P-24-1T-16
Size (L x W x H)	305mm x 216mm x 107mm	305mm x 216mm x 107mm
Spliced Fiber Capacity	144 splices (6 trays x 24)	24 splices (1 tray x 24)
Adapter	No Adapter	16 SC Adapters
Cable Ports (Cable Diameter)	Main Ports	2 x 12mm
	Drop Ports	16 x 5mm